

SwimClear™ mono-élément

Découvrez les 3 nouveaux filtres à éléments filtrants mono cartouche les plus performants du marché. Leur conception innovante a permis d'améliorer considérablement l'hydraulique et les performances de ces filtres.

Les PLUS

- + Optimisation de l'hydraulique : meilleure répartition de l'eau autour de la cartouche, le filtre capture plus de débris.
- + Installation et entretien faciles.
- + Filtration éco-responsable : économe en énergie et en produits chimiques

C100SE

C150SE

C200SE

Élément filtrant facile à retirer



10 ANS
GARANTIE
SUR LA CUVE

5 ANS
GARANTIE
EQUIPEMENTS

Naturally
Hayward

NEW

EFFICACITÉ DE FILTRATION

- Finesse de filtration 2 fois meilleure que celle d'un filtre à sable. Grande capacité de rétention.
- Répartition des débris et une meilleure exploitation de la surface filtrante.
- La finesse de filtration assure une eau claire avec une réduction de l'utilisation des produits chimiques.

PERFORMANCES HYDRAULIQUES


- Pertes de charge très faibles, jusqu'à 10 fois moins importantes que sur un filtre classique.
- Le couplage avec une pompe à vitesse variable permet une optimisation des dépenses énergétiques grâce à une filtration en continu à faible régime.

ENTRETIEN FACILE ET REDUIT

- Très faible encombrement au sol particulièrement adapté aux locaux techniques exigus.
- Ses poignées ergonomiques situées sur la tête et sur le corps du filtre permettent un accès aisé aux éléments filtrant pour faciliter les opérations de maintenance.
- Réduction des fréquences de nettoyages due à une meilleure capacité de rétention.



- 1 Manomètre encastré dans la tête pour une plus grande protection.
- 2 Ses nouvelles poignées situées sur la tête et sur le corps du filtre permettent une manipulation des plus faciles.
- 3 Anneau de verrouillage, easy lok. Il est facile d'accéder aux composants internes.
- 4 Hauteur du filtre de faible dimension. Idéal pour les locaux techniques exigus. Facile à déplacer.
- 5 Bouchon de vidange intégré facilitant le nettoyage et l'hivernage du filtre.



Côtes en mm	A	B	C
C100SE	775	330	464
C150SE	857	330	464
C200SE	984	330	464

SWIMCLEAR™
mono-élément

Surface filtrante effective	Débit de référence (filtre à sable)	E/S	Référence
9,3 m ²	20 m ³ / h	63 mm	C100SE
14 m ²	25 m ³ / h	63 mm	C150SE
18,6 m ²	30 m ³ / h	63 mm	C200SE



POMPES



FILTRES



PROJECTEURS



TRAITEMENT EAU



CONTRÔLE



NETTOYEURS



POMPES À CHALEUR



SwimClear™ Single Element cartridge filter

Discover the three new top-performing single element cartridge filters on the market. Thanks to their innovative design these filters deliver considerably improved hydraulics and performance.

The ADVANTAGES

- + Optimised hydraulics: the filter can capture more debris thanks to the improved distribution of water around the cartridge.
- + Easy to install and maintain.
- + Ecologically responsible filtering using less energy and chemicals.

C100SE



C150SE



C200SE



Easy-to-remove filter cartridge



EFFECTIVE FILTERING

- ▶ Filtering levels twice as fine as with a sand filter. High dirt-holding capacity.
- ▶ Optimal spread of debris for better use of filtering surface.
- ▶ Fine filtering levels provide clear water while using less chemicals.

HYDRAULIC PERFORMANCE


- ▶ Very low head loss, up to 10 times less than with a standard filter.
- ▶ When used with a variable-speed pump delivers minimal energy costs thanks to low-flow continuous filtering.

EVEN EASIER TO MAINTAIN

- ▶ Particularly suitable for small pump rooms as takes up very little floor space.
- ▶ Ergonomic handles on the top and body of the filter provide easy access to the filter cartridges for ease of maintenance.
- ▶ Less frequent cleaning thanks to improved dirt-holding capacity.



- 1 Recessed pressure gauge. Place the head assembly upside down on pool pad.
- 2 Ergonomic grip handles: provide multiple handling locations.
- 3 Easy-lok™ ring design. Quick access to internal components.
- 4 Lowest body height to lift elements.
- 5 Complete built-in drain offering full and fast cleaning for simplified filter draining.



Dimensions in mm	A	B	C
C100SE	775	330	464
C150SE	857	330	464
C200SE	984	330	464

	Effective filtration area	Equivalent flow (sand filter)	In/out	Item
SwimClear™ Single Element	9,3 m²	20 m³/h	63 mm	C100SE
	14 m²	25 m³/h	63 mm	C150SE
	18,6 m²	30 m³/h	63 mm	C200SE



PUMPS



FILTERS



LIGHTING



WATER TREATMENT



AUTOMATION



CLEANERS



HEAT PUMPS

